EMT RYMCO[®] REAL COLOR[®]



- Available in 8 vibrant colors, produced from our standard galvanized EMT.

 Trade sizes 1/2 -4.
- Don't waste time spray-painting or taping we have a full rainbow of color EMT in stock and ready to ship.
- Please note conduit color is for purposes of identification only. Color shades and tones can vary per piece.
- Freedon Coat in the interior for a better wiring.





Diámetro Nominal Nominal Size		Peso 10 tramos Weight 10 Unit Lengths		Diámetro Externo(1) Outside Diameter(1)		Espesor Nominal (2) Nominal Thickness(2)			Piezas x atado Pieces x bundle	Piezas x paquete Pieces x lift
in.	mm.	lb.	kg.	in.	mm.	in.	mm.	Tape Color	rieces x bullule	FIECES X IIIL
1/2"	16	30	13.6	0.706	17.93	0.042	1.07	Black	10	700
3/4"	21	46	20.9	0.922	23.42	0.049	1.25	Red	10	500
1"	27	67	30.4	1.163	29.54	0.057	1.45	Blue	10	300
1 1/4"	35	101	45.8	1.510	38.35	0.065	1.65	Red	5	200
1 1/2"	41	116	52.6	1.740	44.20	0.065	1.65	Black	5	150
2"	53	148	67.1	2.197	55.80	0.065	1.65	-		120
2 1/2"	63	216	98.0	2.875	73.03	0.072	1.83	Control of the Contro		61
3"	78	263	119.3	3.500	88.90	0.072	1.83	A. de C.V.	CONDUI	TuS_A51de_C_
3 1/2"	91	349	158.3	4.000	101.60	0.083	2.11	/ T = 2 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		37
4"	103	393	178.3	4.500	114.30	0.083	2.11	1 Paris	1 > #	30

Nota: Tolerancias Aplicables Note: Applicable Tolerances

* Recubrimiento Hibrido Interior Aislante y Anticorrosivo

* Interior Insulated Coating

Largo/Length: 10 Ft. (3.05m) +1/4 in. (+/6.35mm)

(1) 1/2"-2" +/- 0.005 in. (16-53 +/- 0.13mm), 2 1/2" +/ 0.010 in. (63 +/ 0.25mm),

3" +/- .015 in. (78 +/- 0.38mm), 3 1/2" - 4" +/- 0.020 in. (91 - 103 +/-0.51mm) (2)

Solo informativo no requerimiento UL. For info. Only not a UL requirement.