



IMC

Intermediate Metallic Conduit

RYMCO

C A L I D A D 3 6 0

IMC - Intermediate Metallic Conduit



- * Standards Compliance:
ANSI C80-6
Underwriters Laboratories UL 1242
- * Hot dipped galvanized by immersion with a triple layer of protection against corrosion and abrasion the interior wall is covered with a specially formulated non-corrosive lubricating coating, Freedom Coat.
- * Threads are galvanized after cutting
- * Used for industrial installations in electrical systems
- * Standard length: 10 feet
- * Coupling included



US*

TUBERIA INTERMEDIA UL-1242, INTERMEDIATE METAL CONDUIT STEEL IMC

Diametro Nominal Nominal Size		Peso 10 tramos Weight 10 Unit Lengths		Diametro Externo (1) Outside Diameter (1)		Espesor Nominal (1) Nominal Thickness (1)		Color de tapon Thread Prot. Color	Piezas x atado Pieces x bundle	Piezas x paquete Pieces x lift
in.	mm.	lb.	kg.	in.	mm.	in.	mm.			
1/2"	16	62	28.12	0.815	20.70	0.078	1.97	Yellow	10	350
3/4"	21	84	38.10	1.029	26.26	0.083	2.1	Green	5	250
1"	27	119	53.98	1.290	32.77	0.093	2.35	Orange	5	170
1 1/4"	35	158	71.67	1.638	41.59	0.095	2.41	Green	---	135
1 1/2"	41	194	88.00	1.883	47.82	0.100	2.54	Yellow	---	110
2"	53	256	116.12	2.360	59.93	0.105	2.67	Orange	---	80
2 1/2"	63	441	200.04	2.857	72.57	0.150	3.81	Yellow	---	37
3"	78	543	246.30	3.476	88.29	0.150	3.81	Orange	---	30
3 1/2"	91	629	285.31	3.971	100.86	0.150	3.81	Yellow	---	24
4"	103	700	317.52	4.466	113.44	0.150	3.81	Orange	---	24

Nota: Tolerancias Aplicables Largo/Length: 10 Ft. (3.05m) w/coupling +/- 1/4 in. (+/- 6mm)

Note: Applicable Tolerances (1) Promedio de max. y min. de UL-1242. / Average from max. and min. from UL-1242

Conduit RYMCO, makes no warranties expressed or implied including warranty of merchantability or fitness for a particular purpose. The specifications, descriptions, information and illustrated materials here in are submitted solely for evaluation by others and since the use of its information is not within its control, Conduit RYMCO assumes no obligation or liability for such information and does not guarantee result from the use of said products or the information herein. Reference should be made to the original or primary source data along with standard accepted industry practice. The material included here is from the date of publication and is subject to the possibility of change without prior notice. For certification see contact information.